

523
NPS-ME-94-002

NAVAL POSTGRADUATE SCHOOL

Monterey, California



DATA REDUCTION, ANALYSIS AND
RESULTS OF LACV-30-07 AIR CUSHION
VEHICLE TESTS, FORT STORY, VA
August-September 1993

by

Prof. Young S. Shin, Principal Investigator
LT Eric Hoy, USN

Department of Mechanical Engineering

February 1994

Approved for public release; distribution is unlimited

Prepared for:

Naval Surface Warfare Center
Carderock Division - Annapolis Detachment
Annapolis, MD 20084-5000

FedDocs
D 208.14/2
NPS-ME-94-002

208.1412: NPS-ME-94-002

Naval Postgraduate School
Monterey, California 93943

Real Admiral T. A. Mercer
Superintendent

H. Shull
Provost

This report was prepared in conjunction with research conducted for and funded by the Carderock Division, Naval Surface Warfare Center, Annapolis Detachment, Annapolis.

This report was prepared by:

REPORT DOCUMENTATION PAGE

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instruction, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY(Leave Blank)		2. REPORT DATE 15 February 1994		3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Data Reduction, Analysis and Results of LACV-30-07 Air Cushion Vehicle Tests, Fort Story, VA August~September 1993				5. FUNDING NUMBERS N00167-94-WR-4023	
6. AUTHOR(S) Young S. Shin and Eric Hoy					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Postgraduate School Monterey, CA 93943-5000				8. PERFORMING ORGANIZATION REPORT NUMBER NPS-ME-94-002	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Carderock Division, Naval Surface Warfare Center Annapolis Detachment, Annapolis, MD 20084-5000				10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES The views expressed are those of the authors and do not reflect the official policy or position of DOD or US Government.					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release: Distribution is unlimited.				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The LACV-30-07 Air Cushion Vehicle was instrumented and tested at Fort Story, VA during the months of August~September 1993 by Ed. Thomas, NSWC-Cardrock Division, Annapolis Detachment, Annapolis, MD. The tests include 27 cuts with vehicle speed ranging from 0 to 42 knots and approximate wave height of 0 to 2.5 feet. Two triaxial accelerometers, and a pitch and roll transducer were installed to measure (i) axial, transverse and vertical accelerations and (ii) pitch and roll (in degree) of the vehicle. The test results clearly show that the vibration g-amplitude is extremely low (fraction of 1-g level) for air cushion vehicle and air cushion vehicle itself is acting as a super-damper to reduce the wave-induced vibration response amplitude. The vibration amplitude in terms of g-level may not be the controlling factor, but the combined vehicle dominant frequencies, vibration g-level, and duration may be the definite factors that the superconductor magnet must persist.					
14. SUBJECT TERMS Air Cushion Vehicle, Vibration Criteria, Wave Height, Vibration g-level Pitch and Roll				15. NUMBER OF PAGES	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR		

TABLE OF CONTENTS

	<u>Page</u>
ABSTRACT	1
DESCRIPTION OF TEST DATA ACQUISITION	1
TEST DATA REDUCTION SCHEME	2
TEST DATA ANALYSIS AND RESULTS	7
Time Domain Analysis	
Frequency Domain analysis	
MILITARY STANDARD (MIL-STD-167-1)	20
CONCLUSION AND RECOMMENDATION	22
REFERENCES	24

APPENDICES

- A. TEST SETUP ON LACV-30-07 AIR CUSHION VEHICLE
- B. BROADBAND TEST DATA FOR STARBOARD AND PORTSIDE
TRANSDUCERS
- C. SELECTED NARROWBAND TEST DATA FOR STARBOARD
AND PORTSIDE TRANSDUCERS
- D. PITCH AND ROLL TEST DATA

DATA REDUCTION, ANALYSIS AND RESULTS
OF LACV-30-07 AIR CUSHION VEHICLE TESTS
Fort Story, VA, August~September 1993

by

Young S. Shin, Professor
Eric Hoy, LT USN
Department of Mechanical Engineering
Naval Postgraduate School
Monterey, California 93943

ABSTRACT

The LACV-30-07 Air Cushion Vehicle was instrumented and tested at Fort Story, VA during the months of August~September 1993 by Ed. Thomas, NSWC-Cardrock Division, Annapolis Detachment, Annapolis, MD. The tests include 27 cuts with vehicle speed ranging from 0 to 42 knots and approximate wave height of 0 to 2.5 feet. Two triaxial accelerometers, and a pitch and roll transducer were installed to measure (i) axial, transverse and vertical accelerations and (ii) pitch and roll (in degree) of the vehicle. The test results clearly show that the vibration g-amplitude is extremely low (fraction of 1-g level) for air cushion vehicle and air cushion vehicle itself is acting as a super-damper to reduce the wave-induced vibration response amplitude. The vibration amplitude in terms of g-level may not be the controlling factor, but the combined vehicle dominant frequencies, vibration g-level, and duration may be the definite factors that the superconductor magnet must persist.

DESCRIPTION OF TEST DATA ACQUISITION

The test setup on LACV-30-07 Air Cushion Vehicle was described in detail by Ed. Thomas in Ref.[1]. LACV-30-07 vehicle configuration and two triaxial transducer locations are shown in Figure 1. Ref. [1] is attached in Appendix A. The starboard and portside accelerometers were mounted on hull joiner seams. No additional mass equivalent to superconductor magnet was installed. In addition to accelerometers, a pitch and roll transducer was

mounted in the cabin. All eight signals were fed into an eight channel SONY digital audio tape (DAT) recorder. Twenty-seven test cases were obtained with craft speed ranging from 0 to 42 knots and approximate wave height of 0 to 2.5 feet. The details of 27 test cases are shown in Table 1 where test case is denoted as cut number. Each test case includes eight channels of outputs: stardboard vertical(1), axial(2), transverse(3); portside vertical(4), axial(5), transverse(6); pitch(7) and roll(8).

The test data reduction and analysis scheme is shown in Figure 2. The SONY tape recorder played back test DAT tape and the analog signals were fed into 486 PC-based data acquisition software, EASYEST-LX developed by Keithley Asyst. It was used as a data acquisition system. This PC-based data acquisition system allowed us to digitize the analog signals, convert the units from voltage to acceleration(g's) and stored the digitized test data into the hard disk of 486 PC. Finally, MATLAB software was used to retrieve these test data sequences and perform data processing. MATLAB is a very powerful software tool for signal processing.

TEST DATA REDUCTION SCHEME

Two sets of data reduction and analyses were performed, acceleration in g's for channel 1 through 6, and pitch and roll in degrees for channels 7 and 8. For acceleration measurement, the broadband (0 ~ 1000 Hz) and narrowband(0~50 Hz) data analyses were performed. The broadband data analysis captures the dominant resonant g-amplitudes in frequency domain inherent to craft itself and its machineries. The resonant peaks for pitch and roll of craft motion occur in the frequency range of 0 ~ 5 Hz. The narrowband data analysis was used to look into the details of effects of pitch and roll to vibration g-amplitudes. Channel 7 and 8 test data analysis for pitch and roll (0~15 Hz) was also performed. The broadband data for all 27 test cases were documented in Appendix B and the selected narrowband data in Appendix C. The pitch and roll data for all 27 test cases were documented in Appendix D.

Broadband Data Analysis (Channel 1 through 6):


- Sampling Frequency (f_s) = 2,000 Hz
- Maximum Cutoff Frequency ($f_{\max} = f_s/2$) = 1,000 Hz
- Total Number of Sampling Data Points (N) = 1.024×10^5
- Time Step Resolution ($\Delta t = 1/f_s$) = 0.0005 sec.
- Total Time Span Used ($T = N \times \Delta t$) = 51.2 sec.
- Reference 0 GdB (g_{ref}) = 10^{-6} g
- Frequency Domain FFT analysis:
 - Size of Blocks (n) = 4,096 points /block
 - Number of Blocks (M) = 25 blocks

Narrowband Data Analysis (Channel 1 through 6):

- Sampling Frequency (f_s) = 100 Hz
- Maximum Cutoff Frequency ($f_{\max} = f_s/2$) = 50 Hz
- Total Number of Sampling Data Points (N) = 8,192
- Time Step Resolution ($\Delta t = 1/f_s$) = 0.01 sec.
- Total Time Span Used ($T = N \times \Delta t$) = 81.92 sec.
- Frequency Domain FFT analysis:
 - Size of Blocks (n) = 4,096 points /block
 - Number of Blocks (M) = 2 blocks

Pitch and Roll Data Analysis (Channels 7 and 8):

- Sampling Frequency (f_s) = 100 Hz
- Maximum Cutoff Frequency ($f_{\max} = f_s/2$) = 50 Hz
- Total Number of Sampling Data Points (N) = 8,192
- Time Step Resolution ($\Delta t = 1/f_s$) = 0.01 sec.
- Total Time Span Used ($T = N \times \Delta t$) = 81.92 sec.
- Frequency Domain FFT analysis:
 - Size of Blocks (n) = 4,096 points /block
 - Number of Blocks (M) = 2 blocks



	Length(ft)	Width(ft)
LACV-30	74.92	35.93
Cargo Deck	49.85	31.28

Figure 1. LACV-30 Air Cushion Vehicle and Transducer Locations




Figure 2. Data Acquisition, Reduction and Processing Scheme

DATA FOR ACV 30-07 ACCELERATION EVALUATION

<u>CUT#</u>	<u>TAPE TIME</u>	<u>SPEED KNOTS</u>	<u>WAVE HEIGHT FEET</u>
1	12:57	22.5	1.5
2	13:02	19	1.5
3	13:46	32	1.5
4	13:52	42	0
6	07:01	36	0
7	07:12	25	0
8	07:20	35	0
9	08:28	0	0
10	08:31	36	0
11	08:43	6.2	0
12	08:50	15	0
13	09:03	0	on land
14	09:15	0	on land
15	09:32	30.8	1
16	09:36	27	2
17	09:54	35	2
18	10:07	18	2.5
19	10:14	8	2.5
20	10:25	16	2.5
21	10:28	25	2.5
22	10:33	10	2.5
23	10:38	36	2.5
24	10:52	22	2.5
25	10:57	25	2.5
26	11:20	30	2.5
27	11:27	31	2.5

Channel 1--Stbd Vertical

Channel 4--Port Vertical

Channel 2--Stbd Axial

Channel 5--Port Axial

Channel 3--Stbd Transverse

Channel 6--Port Transverse

For the above: 1 volt(rms)=1 g(rms)

Channel 7--Pitch

Channel 8--Roll

For the above: 1 volt=5 degrees of vessel rotation

Table 1. Description of Each Test Case

TEST DATA ANALYSIS AND RESULTS

All 27 test cases are tabulated in histogram as shown in Figure 3 in terms of craft speed and wave height. The test case 5 data was bad and not analyzed. Both time and frequency domain analyses were performed:

Time Domain Analysis

For each measurement (i.e., starboard vertical acceleration, etc.), digitized time domain data was obtained and included in Appendices B through D. It was used to determine the peak vibration response. The peak accelerations in vertical, axial and transverse directions at both starboard and portside were quantified and tabulated. Figure 4 shows the peak starboard acceleration in all three directions. The maximum accelerations in vertical, axial and transverse directions are 0.60g (test case 2), 0.27g (test case 13), and 0.30g (test case 15). Figure 5 shows the peak portside acceleration in all three directions. The maximum accelerations in vertical, axial and transverse directions are 0.35g (test case 2), 0.39g (test cases 16 & 21), and 0.30g (test case 13). Figure 6 shows the peak pitch and roll in degree for all 27 cases. The maximum pitch is 5.0 degrees (test case 1) and roll is 2.2 degrees (test case 1). Figure 7 tabulated vertical accelerations in histogram. and it shows that starboard vertical acceleration is generally higher than that of portside. Figure 8 tabulated axial accelerations in histogram. and it shows that portside axial acceleration is generally higher than that of portside. Figure 9 tabulated transverse accelerations in histogram. and it shows that starboard vertical acceleration in generally higher than that of portside. We do not observe any definite correlation of the measured quantities to craft speed and wave height.

As observed the measured accelerations, the maximum peak acceleration magnitude is the fraction of 1-g which implies that air cushion vehicle itself is acting well as a super-damper to reduce the wave-induced vibration response amplitude. For pitch and roll, except test case 1, the average value is less than 2 degrees.

Frequency Domain Analysis

Each measurement (i.e., starboard vertical acceleration, etc.), Fast Fourier Transform(FFT) was computed and displayed in Appendices B through D.

As observed in the Appendix B, broadband vibration-g FFT data, there are dominant peaks at approximately 90 Hz and its harmonics which may be the craft and its machinery toner frequency and its harmonic. It also displays good size peaks at approximately 60 Hz and its harmonics which may be inherent to the craft and its machinery characteristics. One of the FFT was depicted from Appendix B and shown in Figure 10. In addition to 60 Hz and 90 Hz components, there is also a dominant peak at near zero frequency which is effected by pitch and roll of the craft. The dominant frequencies of pitch and roll were in the range of 0~5 Hz (Appendix D).

To look into the details of pitch and roll, FFT was computed in lower frequency range and displayed in Appendix D. Sample pitch and roll FFTs were depicted from Appendix D and shown in Figures 11 and 12. The dominant frequency of pitch is about 1 Hz and for roll it is even lower than 1 Hz.

As mentioned above, the broadband FFT analysis results (Appendix B) showed that there is a dominant peak at near zero frequency. The narrowband analysis was performed to look into the effect of pitch and roll. One of the FFT was depicted from Appendix C and shown in Figure 13. There is a dominant peak at about 1 Hz which is also pitch frequency. Based on the observation of Appendix C: Narrowband Data, roll and pitch of the craft affect the vibration-g responses at both starboard and portside.

LACV-30-07 CRAFT TEST, FORT STORY, VA




Figure 3. Craft Speeds and Wave Heights for All Test Cases

LACV-30-07 CRAFT TEST, FORT STORY, VA




Figure 4 Peak Starboard Acceleration (g's) in Vertical Axial and Transverse Directions for All Test Cases

LACV-30-07 CRAFT TEST, FORT STORY, VA




Figure 5. Peak Portside Acceleration (g's) in Vertical, Axial and Transverse Directions for All Test Cases

LACV-30-07 CRAFT TEST, FORT STORY, VA




Figure 6. Peak Pitch and Roll (Deg.) for All Test Cases

LACV-30-07 CRAFT TEST, FORT STORY, VA




Figure 7. Peak Vertical Acceleration at Starboard and Portside in All Test Cases

LACV-30-07 CRAFT TEST, FORT STROY, VA




Figure 8 Peak Axial Acceleration at Starboard and Portside in All Test Cases

LACV-30-07 CRAFT TEST, FORT STORY, VA




Figure 9. Peak Transverse Acceleration at Starboard and Portside in All Test Cases




Figure 10. Broadband Sample Acceleration Data

cut1-22.5kts-1.5ft: pitch




Figure 11. Sample Data for Pitch (FFT)




Figure 12. Sample Data for Roll (FFT)

cut2-19kts-1.5ft:stbd vert(narrowband)




Figure 13. Narrowband Sample FFT Data

MILITARY STANDARD [MIL-STD-167-1 (SHIPS)] MECHANICAL VIBRATIONS OF SHIPBOARD EQUIPMENT

This standard [Ref. 2] covers the requirements of Naval shipboard equipment including machinery as regards externally imposed vibrations. The standard covers Type I (Environmental vibration) and Type II (Internally excited vibration). For superconductor magnet, it belongs to Type I classification. Type I applies to all equipment intended for shipboard use or which must be capable of withstanding the environmental vibration conditions which may be encountered aboard naval ships (Section 1.3).

The standard requires to perform the variable frequency test ranging from 4 Hz to 50 Hz with frequency interval of 1 Hz with the vibration stroke amplitude shown in the table 2 below. At each frequency interval, vibration shall be maintained for 5 minutes (Section 5.1). The tests are to be performed one direction at the time (vertical, fore and aft, and athwartship).

Frequency Range (Hz)	Table Amplitude (inch)	Range of g-Level
04 - 15	0.030 +/- 0.006	0.06 ~ 0.8
16 - 25	0.020 +/- 0.004	0.60 ~ 1.3
26 - 33	0.010 +/- 0.002	0.80 ~ 1.25
34 - 40	0.005 +/- 0.001	0.73 ~ 0.90
41 - 50	0.003 +/- 0.000	0.60 ~ 0.83

Table 2. Type I Vibration Test Criterion

There is also provision for exception to make the vibration test more inclusive. Type I environmental vibration limits figure (taken from standard) is shown in Figure 14.




Figure 14. Type I Environmental Vibration Limits
(MIL-STD-167-1)

CONCLUSIONS AND RECOMMENDATION

The LACV-30-07 Air Cushion Vehicle Test provided the valuable vibration data even if the craft is not mass loaded which is equivalent to the mass of the superconductor magnet. The reduced test data showed that the peak vibration amplitude is in the order of fraction of 1-g level. The dominant frequencies include (i) 0 ~ 5 Hz for pitch and roll, and (2) strong 90 Hz and its harmonics, and weak 60 Hz and its harmonics which are inherent to the craft and its machinery. For various craft types, the various discrete frequency components would appear. The vibration amplitude in terms of g-level may not be the only controlling factor, but the combined vehicle dominant frequencies, vibration g-level, and duration may be the definite factors that the superconductor magnet must persist.

Projecting the LACV-30-07 test results into the MIL-STD-167-1, the following recommendations are made.

(1) The 0 to 4 Hz frequency range is to be included in vibration design criteria to take into account of pitch and roll of craft. In the upper frequency range, 60 Hz to 100 Hz frequency range is to be included in vibration design criterion to take into account of mostly craft machinery vibrations. The proposed vibration design criteria must be upperbound given in MIL-STD-167-1. The proposed vibration design criteria is shown in Figure 15. For the frequency range of 0~3 Hz, a constant vibration stroke length (displacement) of 40 mils is recommended.

(2) The recommended duration of vibration for each frequency range is shown below.

- | | | |
|-------|--------------|---------------------------------|
| (i) | 0 ~ 3 Hz: | 5 minutes every 0.5 Hz interval |
| (ii) | 4 ~ 50 Hz: | 5 minutes every 1.0 Hz interval |
| (iii) | 51 ~ 100 Hz: | 3 minutes every 2.0 Hz interval |




Figure 15. Proposed Vibration Design Criteria for Superconductor Magnet

(3) The direction of vibration excitation given to the superconductor magnet must be vertical, fore and aft, and athwartship, one direction at the time. The input motion must be applied to the support points of superconductor magnet.

The above recommendation is preliminary in nature but somewhat comfortable and conservative. The deformations and stresses induced by the above vibration design criteria are important. But also the vibration-induced quenching criteria must be developed using mainly experimental approach.

REFERENCE

1. Ed. Thomas, "Report Input - Test Setup on LACV-30-07 Fort Story, VA, August~September 1993", October 1993.
2. MIL-STD-167-1 (SHIPS), "Mechanical Vibrations of Shipboard Equipment", 1 May 1974.

APPENDIX A

Test Setup on LACV-30-07 Air Cushion Vehicle

Fort Story, VA

August - September 1993

Report Input by Ed Thomas

Test Setup on LACV-30-07 Fort Story, VA August-September 1993.

The LACV-30-07 craft was instrumented at Fort Story, VA by Code 812 and a Corporal from the maintenance group. Two triaxial blocks were installed carrying three ground isolated accelerometers in vertical, axial, and transverse directions. The starboard triaxial block was mounted about ten feet aft of the bow of the craft above the center - starboard hull joiner seam. The port triaxial block was mounted about thirteen feet aft of the bow above the center - port hull joiner seam. These locations were picked as typical of foundation mounting points for an ALISS superconducting minesweeping magnet. The cabling to these accelerometers was waterproofed with silicone caulk coated with a triple wrap of electrical tape. The cabling was taken aft to the cabin of the vessel. The accelerometers used were internally amplified, low noise, 100 millivolt/g units. These units were powered and amplified to a final sensitivity of 1 volt/g. The signals were fed to an eight channel digital audio tape (DAT) recorder in the cabin. A pitch and roll transducer with a sensitivity of ten degrees/volt was oriented and mounted in the cabin above the radio and DAT recorder. Pitch and roll signals were recorded as the final two signals of the DAT recorder. A global positioning system (GPS) antenna was mounted on the port rail outside the cabin to allow satellite reception and yield true heading and speed of the vessel during testing. The vessel instrumentation had no speed readout.

The GPS system readout was placed in the cabin and energized by the vessels battery. The original plan for the testing of the vibration base of the LACV-30-07 evaluations were to take data cuts at 5 knot increments from hover to maximum speed in calm water and in as rough water as weather and craft limits allow (about Sea State 3). The speed of the LACV-30 craft are very difficult to control in precise increments due to the very low drag when the vehicle is on cushion. We tried hard to obtain data about 15 knots, but could not maintain this speed for two minutes recording time. Fifteen knots is believed to be the in the middle of the "hump" range of these vehicles. Rough water testing (2.5 foot waves) was carried out heading into the sea as much as possible.

Analysis of Data Collected Toward ALISS Component Durability Specification

The data collected was analyzed with Fast Fourier Transform (FFT) analyzer using 800 line analysis from 0 - 1 kiloHertz with 200 data averages. All accelerometer data was analyzed in this manner. The output of the analyzer was reduced to hard copy and disk storage. The typical rough water data collected had a low frequency hump due to wave action on the cushion and eventually the vessel from the cushion. Machinery noise tonals and their harmonics were of nearly similar level to the wave induced vibration in the vertical direction. The acceleration spectrum levels reduced from the tape recorded data were combined by power summation techniques to a single acceleration spectrum level (A_m).

In order to increase readability and accuracy of the wave action acceleration of the vessel, a series of 0 - 50 Hz analyses were conducted on the data along with pitch and roll transducer data. This analysis was carried out by the same FFT system using 400 line analysis with 100 averages. A similar power summing procedure as described above was carried out with the low frequency spectra to a single acceleration spectrum (A_w).

Specification Development

It is desired to generate a component design specification spectra for ALISS component development contractors that is conservative, but not too conservative. The purpose of this spectra is to provide a pass - fail shaker input spectra to insure deployed operation of research - early development magnetic minesweeping components. The LACV-30 measurements were lower than expected for a proposed ALISS operational vehicle, such as a helicopter or LCAC. The specification should entail vessel operation in Sea State 3 and operation with some degree of vibration increase due to machinery degradation.

The peak values of the two power summed spectra were combined by the equation $A_s \sim 20 \times \log(4 \times A_w + 2 \times A_m)$ as an ALISS component survivability specification for early responding contractors to test prototype units to for durability. This specification will probably be modified by the output of the data analysis presently underway at the Naval Postgraduate School.

APPENDIX B

BROADBAND TEST DATA FOR STARBOARD AND PORTSIDE TRIAXIAL TRANSDUCERS

cut1-25kts-1.5ft: stbd vert

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005637 G

Standard deviation = 0.1914 G

The plot shows 1024 data points



cut1-25kts-1.5ft: stbd vert



cut1-25kts-1.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002213 G

Standard deviation = 0.04581 G

The plot shows 1024 data points



cut1-25kts-1.5ft: stbd axial



cut1-25kts-1.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003151 G

Standard deviation = 0.05582 G

The plot shows 1024 data points



cut1-25kts-1.5ft: stbd transverse



cut1-25kts-1.5ft: port vert

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002249 G

Standard deviation = 0.1032 G

The plot shows 1024 data points



cut1-25kts-1.5ft: port vert



cut1-25kts-1.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003437 G

Standard deviation = 0.08655 G

The plot shows 1024 data points



cut1-25kts-1.5ft: port axial



cut1-25kts-1.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.00467 G

Standard deviation = 0.04559 G

The plot shows 1024 data points



cut1-25kts-1.5ft: port transverse



cut2-19kts-1.5ft: stbd vert

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.0007665 G

Standard deviation = 0.1567 G

The plot shows 1024 data points



cut2-19kts-1.5ft: stbd vert



cut2-19kts-1.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003627 G

Standard deviation = 0.03808 G

The plot shows 1024 data points



cut2-19kts-1.5ft: stbd axial



cut2-19kts-1.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.00188 G

Standard deviation = 0.04881 G

The plot shows 1024 data points



cut2-19kts-1.5ft: stbd transverse



cut2-19kts-1.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0009212 G

Standard deviation = 0.08587 G

The plot shows 1024 data points



cut2-19kts-1.5ft: port vertical



cut2-19kts-1.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002842 G

Standard deviation = 0.07925 G

The plot shows 1024 data points



cut2-19kts-1.5ft: port axial



cut2-19kts-1.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.00358 G

Standard deviation = 0.04249 G

The plot shows 1024 data points



cut2-19kts-1.5ft: port transverse



cut3-32kts-1.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.01474 G

Standard deviation = 0.1137 G

The plot shows 1024 data points



cut3-32kts-1.5ft: stbd vertical



cut3-32kts-1.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.006655 G

Standard deviation = 0.04294 G

The plot shows 1024 data points



cut3-32kts-1.5ft: stbd axial



cut3-32kts-1.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005751 G

Standard deviation = 0.05294 G

The plot shows 1024 data points



cut3-32kts-1.5ft: stbd transverse



cut3-32kts-1.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.008313 G

Standard deviation = 0.07156 G

The plot shows 1024 data points



cut3-32kts-1.5ft: port vertical



cut3-32kts-1.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.008567 G

Standard deviation = 0.08785 G

The plot shows 1024 data points



cut3-32kts-1.5ft: port axial



cut3-32kts-1.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003843 G

Standard deviation = 0.04345 G

The plot shows 1024 data points



cut3-32kts-1.5ft: port transverse



cut4-42kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.005961 G

Standard deviation = 0.1105 G

The plot shows 1024 data points



cut4-42kts-0ft: stbd vertical



cut4-42kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003196 G

Standard deviation = 0.04388 G

The plot shows 1024 data points



cut4-42kts-0ft: stbd axial



cut4-42kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003802 G

Standard deviation = 0.05432 G

The plot shows 1024 data points



cut4-42kts-0ft: stbd transverse



cut4-42kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.003514 G

Standard deviation = 0.0712 G

The plot shows 1024 data points



cut4-42kts-0ft: port vertical



cut4-42kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.001524 G

Standard deviation = 0.09251 G

The plot shows 1024 data points



cut4-42kts-0ft: port axial



cut4-42kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001482 G

Standard deviation = 0.04555 G

The plot shows 1024 data points



cut4-42kts-0ft: port transverse



cut6-36kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003913 G

Standard deviation = 0.1098 G

The plot shows 1024 data points



cut6-36kts-0ft: stbd vertical



cut6-36kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003436 G

Standard deviation = 0.03529 G

The plot shows 1024 data points



cut6-36kts-0ft: stbd axial



cut6-36kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004032 G

Standard deviation = 0.04704 G

The plot shows 1024 data points



cut6-36kts-0ft: stbd transverse



cut6-36kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003014 G

Standard deviation = 0.06849 G

The plot shows 1024 data points



cut6-36kts-0ft: port vertical



cut6-36kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002169 G

Standard deviation = 0.07616 G

The plot shows 1024 data points



cut6-36kts-0ft: port axial



cut6-36kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002153 G

Standard deviation = 0.04091 G

The plot shows 1024 data points



cut6-36kts-0ft: port transverse



cut7-25kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.01362 G

Standard deviation = 0.1235 G

The plot shows 1024 data points



cut7-25kts-0ft: stbd vertical



cut7-25kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005764 G

Standard deviation = 0.0357 G

The plot shows 1024 data points



cut7-25kts-0ft: stbd axial



cut7-25kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.006373 G

Standard deviation = 0.04685 G

The plot shows 1024 data points



cut7-25kts-0ft: stbd transverse



cut7-25kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.007335 G

Standard deviation = 0.07302 G

The plot shows 1024 data points



cut7-25kts-0ft: port vertical



cut7-25kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005625 G

Standard deviation = 0.07448 G

The plot shows 1024 data points



cut7-25kts-0ft: port axial



cut7-25kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004059 G

Standard deviation = 0.04028 G

The plot shows 1024 data points



cut7-25kts-0ft: port transverse



cut8-35kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.009605 G

Standard deviation = 0.1327 G

The plot shows 1024 data points



cut8-35kts-0ft: stbd vertical



cut8-35kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003532 G

Standard deviation = 0.04705 G

The plot shows 1024 data points



cut8-35kts-0ft: stbd axial



cut8-35kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002441 G

Standard deviation = 0.05189 G

The plot shows 1024 data points



cut8-35kts-0ft: stbd transverse



cut8-35kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.001443 G

Standard deviation = 0.0805 G

The plot shows 1024 data points



cut8-35kts-0ft: port vertical



cut8-35kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004101 G

Standard deviation = 0.09179 G

The plot shows 1024 data points



cut8-35kts-0ft: port axial



cut8-35kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001882 G

Standard deviation = 0.04526 G

The plot shows 1024 data points



cut8-35kts-0ft: port transverse



cut9-0kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.01364 G

Standard deviation = 0.03499 G

The plot shows 1024 data points



cut9-0kts-0ft: stbd vertical



cut9-0kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.00667 G

Standard deviation = 0.01369 G

The plot shows 1024 data points



cut9-0kts-0ft: stbd axial



cut9-0kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.006449 G

Standard deviation = 0.01397 G

The plot shows 1024 data points



cut9-0kts-0ft: stbd transverse



cut9-0kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.005235 G

Standard deviation = 0.01778 G

The plot shows 1024 data points



cut9-0kts-0ft: port vertical



cut9-0kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005631 G

Standard deviation = 0.01426 G

The plot shows 1024 data points



cut9-0kts-0ft: port axial



cut9-0kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.0006278 G

Standard deviation = 0.009576 G

The plot shows 1024 data points



cut9-0kts-0ft: port transverse



cut10-36kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004197 G

Standard deviation = 0.1458 G

The plot shows 1024 data points



cut10-36kts-0ft: stbd vertical



cut10-36kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005945 G

Standard deviation = 0.05191 G

The plot shows 1024 data points



cut10-36kts-0ft: stbd axial



cut10-36kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.006841 G

Standard deviation = 0.06371 G

The plot shows 1024 data points



cut10-36kts-0ft: stbd transverse



cut10-36kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004521 G

Standard deviation = 0.08574 G

The plot shows 1024 data points



cut10-36kts-0ft: port vertical



cut10-36kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.01038 G

Standard deviation = 0.1022 G

The plot shows 1024 data points



cut10-36kts-0ft: port axial



cut10-36kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004115 G

Standard deviation = 0.0535 G

The plot shows 1024 data points



cut10-36kts-0ft: port transverse



cut11-6.2kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.01076 G

Standard deviation = 0.1022 G

The plot shows 1024 data points



cut11-6.2kts-0ft: stbd vertical



cut11-6.2kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004406 G

Standard deviation = 0.02935 G

The plot shows 1024 data points



cut11-6.2kts-0ft: stbd axial



cut11-6.2kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003997 G

Standard deviation = 0.053 G

The plot shows 1024 data points



cut11-6.2kts-0ft: stbd transverse



cut11-6.2kts-0ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.007631 G

Standard deviation = 0.05474 G

The plot shows 1024 data points



cut11-6.2kts-0ft: port vertical



cut11-6.2kts-0ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.009207 G

Standard deviation = 0.08172 G

The plot shows 1024 data points



cut11-6.2kts-0ft: port axial



cut11-6.2kts-0ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002013 G

Standard deviation = 0.03597 G

The plot shows 1024 data points



cut11-6.2kts-0ft: port transverse



cut12-15kts-0ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.003885 G

Standard deviation = 0.09368 G

The plot shows 1024 data points



cut12-15kts-0ft: stbd vertical



cut12-15kts-0ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002857 G

Standard deviation = 0.0293 G

The plot shows 1024 data points



cut12-15kts-0ft: stbd axial



cut12-15kts-0ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5


* The time domain

Mean value = -0.004502 G

Standard deviation = 0.0502 G

The plot shows 1024 data points





cut12-15kts-0ft:port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001611 G

Standard deviation = 0.05888 G

The plot shows 1024 data points



cut12-15kts-0ft:port vertical



cut12-15kts-0ft:port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.00365 G

Standard deviation = 0.08218 G

The plot shows 1024 data points



cut12-15kts-0ft:port axial



cut12-15kts-0ft:port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002002 G

Standard deviation = 0.03743 G

The plot shows 1024 data points



cut12-15kts-0ft:port transverse



cut13-on land hover: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.05456 G

Standard deviation = 0.1765 G

The plot shows 1024 data points



cut13-on land hover: stbd vertical



cut13-on land hover: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.009881 G

Standard deviation = 0.07022 G

The plot shows 1024 data points



cut13-on land hover: stbd axial



cut13-on land hover: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.009395 G

Standard deviation = 0.09401 G

The plot shows 1024 data points



cut13-on land hover: stbd transverse



cut13-on land hover: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.02228 G

Standard deviation = 0.1129 G

The plot shows 1024 data points



cut13-on land hover: port vertical



cut13-on land hover: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004777 G

Standard deviation = 0.1544 G

The plot shows 1024 data points



cut13-on land hover: port axial



cut13-on land hover: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0009341 G

Standard deviation = 0.07733 G

The plot shows 1024 data points



cut13-on land hover: port transverse



cut14-on land hover: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.01895 G

Standard deviation = 0.1304 G

The plot shows 1024 data points



cut14-on land hover: stbd vertical



cut14-on land hover: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.002877 G

Standard deviation = 0.05181 G

The plot shows 1024 data points



cut14-on land hover: stbd axial



cut14-on land hover: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0002529 G

Standard deviation = 0.0808 G

The plot shows 1024 data points



cut14-on land hover: stbd transverse



cut14-on land hover: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.007709 G

Standard deviation = 0.0884 G

The plot shows 1024 data points



cut14-on land hover: port vertical



cut14-on land hover: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.01427 G

Standard deviation = 0.1427 G

The plot shows 1024 data points



cut14-on land hover: port axial



cut14-on land hover: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.007547 G

Standard deviation = 0.06265 G

The plot shows 1024 data points



cut14-on land hover: port transverse



cut15-30.8kts-1ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.008574 G

Standard deviation = 0.1622 G

The plot shows 1024 data points



cut15-30.8kts-1ft: stbd vertical



cut15-30.8kts-1ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.006409 G

Standard deviation = 0.04744 G

The plot shows 1024 data points



cut15-30.8kts-1ft: stbd axial



cut15-30.8kts-1ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.006388 G

Standard deviation = 0.06553 G

The plot shows 1024 data points



cut15-30.8kts-1ft: stbd transverse



cut15-30.8kts-1ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.007183 G

Standard deviation = 0.09177 G

The plot shows 1024 data points



cut15-30.8kts-1ft: port vertical



cut15-30.8kts-1ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004441 G

Standard deviation = 0.101 G

The plot shows 1024 data points



cut15-30.8kts-1ft: port axial



cut15-30.8kts-1ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0009481 G

Standard deviation = 0.05086 G

The plot shows 1024 data points



cut15-30.8kts-1ft: port transverse



cut16-27kts-2ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.007548 G

Standard deviation = 0.148 G

The plot shows 1024 data points



cut16-27kts-2ft: stbd vertical



cut16-27kts-2ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005931 G

Standard deviation = 0.05278 G

The plot shows 1024 data points



cut16-27kts-2ft: stbd axial



cut16-27kts-2ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.006509 G

Standard deviation = 0.07155 G

The plot shows 1024 data points



cut16-27kts-2ft: stbd transverse



cut16-27kts-2ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004309 G

Standard deviation = 0.08824 G

The plot shows 1024 data points



cut16-27kts-2ft: port vertical



cut16-27kts-2ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.006124 G

Standard deviation = 0.1067 G

The plot shows 1024 data points



cut16-27kts-2ft: port axial



cut16-27kts-2ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002992 G

Standard deviation = 0.05687 G

The plot shows 1024 data points



cut16-27kts-2ft: port transverse



cut17-35kts-2ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.00349 G

Standard deviation = 0.1209 G

The plot shows 1024 data points



cut17-35kts-2ft: stbd vertical



cut17-35kts-2ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005779 G

Standard deviation = 0.0407 G

The plot shows 1024 data points



cut17-35kts-2ft: stbd axial



cut17-35kts-2ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.007786 G

Standard deviation = 0.06173 G

The plot shows 1024 data points



cut17-35kts-2ft: stbd transverse



cut17-35kts-2ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004295 G

Standard deviation = 0.07304 G

The plot shows 1024 data points



cut17-35kts-2ft: port vertical



cut17-35kts-2ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.008993 G

Standard deviation = 0.0943 G

The plot shows 1024 data points



cut17-35kts-2ft: port axial



cut17-35kts-2ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004266 G

Standard deviation = 0.04773 G

The plot shows 1024 data points



cut17-35kts-2ft: port transverse



cut18-18kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001693 G

Standard deviation = 0.1271 G

The plot shows 1024 data points



cut18-18kts-2.5ft: stbd vertical



cut18-18kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005407 G

Standard deviation = 0.03587 G

The plot shows 1024 data points



cut18-18kts-2.5ft: stbd axial



cut18-18kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0065 G

Standard deviation = 0.05731 G

The plot shows 1024 data points



cut18-18kts-2.5ft: stbd transverse



cut18-18kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002557 G

Standard deviation = 0.07528 G

The plot shows 1024 data points



cut18-18kts-2.5ft: port vertical



cut18-18kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.0008875 G

Standard deviation = 0.09207 G

The plot shows 1024 data points



cut18-18kts-2.5ft: port axial



cut18-18kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002346 G

Standard deviation = 0.04684 G

The plot shows 1024 data points



cut18-18kts-2.5ft: port transverse



cut19-8kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002368 G

Standard deviation = 0.09414 G

The plot shows 1024 data points



cut19-8kts-2.5ft: stbd vertical



cut19-8kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.002 G

Standard deviation = 0.03176 G

The plot shows 1024 data points



cut19-8kts-2.5ft: stbd axial



cut19-8kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.004747 G

Standard deviation = 0.04767 G

The plot shows 1024 data points



cut19-8kts-2.5ft: stbd transverse



cut19-8kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.002627 G

Standard deviation = 0.06034 G

The plot shows 1024 data points



cut19-8kts-2.5ft: port vertical



cut19-8kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.00387 G

Standard deviation = 0.08631 G

The plot shows 1024 data points



cut19-8kts-2.5ft: port axial



cut19-8kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.004134 G

Standard deviation = 0.03828 G

The plot shows 1024 data points



cut19-8kts-2.5ft: port transverse



cut20-16kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = 0.0004143 G

Standard deviation = 0.106 G

The plot shows 1024 data points



cut20-16kts-2.5ft: stbd vertical



cut20-16kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002002 G

Standard deviation = 0.03096 G

The plot shows 1024 data points



cut20-16kts-2.5ft: stbd axial



cut20-16kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002442 G

Standard deviation = 0.06437 G

The plot shows 1024 data points



cut20-16kts-2.5ft: stbd transverse



cut20-16kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002996 G

Standard deviation = 0.06604 G

The plot shows 1024 data points



cut20-16kts-2.5ft: port vertical



cut20-16kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0001399 G

Standard deviation = 0.09214 G

The plot shows 1024 data points



cut20-16kts-2.5ft: port axial



cut20-16kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001848 G

Standard deviation = 0.03979 G

The plot shows 1024 data points



cut20-16kts-2.5ft: port transverse



cut21-25kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001856 G

Standard deviation = 0.143 G

The plot shows 1024 data points



cut21-25kts-2.5ft: stbd vertical



cut21-25kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.008223 G

Standard deviation = 0.03278 G

The plot shows 1024 data points



cut21-25kts-2.5ft: stbd axial



cut21-25kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004448 G

Standard deviation = 0.07815 G

The plot shows 1024 data points



cut21-25kts-2.5ft: stbd transverse



cut21-25kts-2.5ft: port verticale

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.001224 G

Standard deviation = 0.07974 G

The plot shows 1024 data points



cut21-25kts-2.5ft: port verticale



cut21-25kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.00978 G

Standard deviation = 0.0946 G

The plot shows 1024 data points



cut21-25kts-2.5ft: port axial



cut21-25kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003377 G

Standard deviation = 0.04006 G

The plot shows 1024 data points



cut21-25kts-2.5ft: port transverse



cut22-10kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004114 G

Standard deviation = 0.1105 G

The plot shows 1024 data points



cut22-10kts-2.5ft: stbd vertical



cut22-10kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.001426 G

Standard deviation = 0.032 G

The plot shows 1024 data points



cut22-10kts-2.5ft: stbd axial



cut22-10kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002691 G

Standard deviation = 0.07573 G

The plot shows 1024 data points



cut22-10kts-2.5ft: stbd transverse



cut22-10kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004157 G

Standard deviation = 0.07039 G

The plot shows 1024 data points



cut22-10kts-2.5ft: port vertical



cut22-10kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003256 G

Standard deviation = 0.1004 G

The plot shows 1024 data points



cut22-10kts-2.5ft: port axial



cut22-10kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0009181 G

Standard deviation = 0.03994 G

The plot shows 1024 data points



cut22-10kts-2.5ft: port transverse



cut23-36kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.006317 G

Standard deviation = 0.1707 G

The plot shows 1024 data points



cut23-36kts-2.5ft: stbd vertical



cut23-36kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.00339 G

Standard deviation = 0.04875 G

The plot shows 1024 data points



cut23-36kts-2.5ft: stbd axial



cut23-36kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.004388 G

Standard deviation = 0.07592 G

The plot shows 1024 data points



cut23-36kts-2.5ft: stbd transverse



cut23-36kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005653 G

Standard deviation = 0.09345 G

The plot shows 1024 data points



cut23-36kts-2.5ft: port vertical



cut23-36kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004554 G

Standard deviation = 0.1053 G

The plot shows 1024 data points



cut23-36kts-2.5ft: port axial



cut23-36kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003551 G

Standard deviation = 0.05403 G

The plot shows 1024 data points



cut23-36kts-2.5ft: port transverse



cut24-22kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005581 G

Standard deviation = 0.2144 G

The plot shows 1024 data points



cut24-22kts-2.5ft: stbd vertical



cut24-22kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.006091 G

Standard deviation = 0.04788 G

The plot shows 1024 data points



cut24-22kts-2.5ft: stbd axial



cut24-22kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.0004403 G

Standard deviation = 0.07778 G

The plot shows 1024 data points



cut24-22kts-2.5ft: stbd transverse



cut24-22kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002009 G

Standard deviation = 0.05394 G

The plot shows 1024 data points



cut24-22kts-2.5ft: port transverse



cut24-22kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002827 G

Standard deviation = 0.103 G

The plot shows 1024 data points



cut24-22kts-2.5ft: port axial



cut24-22kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.002214 G

Standard deviation = 0.1115 G

The plot shows 1024 data points



cut24-22kts-2.5ft: port vertical



cut25-25kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.00707 G

Standard deviation = 0.1757 G

The plot shows 1024 data points



cut25-25kts-2.5ft: stbd vertical



cut25-25kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.006864 G

Standard deviation = 0.04503 G

The plot shows 1024 data points



cut25-25kts-2.5ft: stbd axial



cut25-25kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.005649 G

Standard deviation = 0.07015 G

The plot shows 1024 data points



cut25-25kts-2.5ft: stbd transverse



cut25-25kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.005041 G

Standard deviation = 0.09403 G

The plot shows 1024 data points



cut25-25kts-2.5ft: port vertical



cut25-25kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.008277 G

Standard deviation = 0.09461 G

The plot shows 1024 data points



cut25-25kts-2.5ft: port axial



cut25-25kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.00372 G

Standard deviation = 0.04955 G

The plot shows 1024 data points



cut25-25kts-2.5ft: port transverse



cut26-30kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.009343 G

Standard deviation = 0.154 G

The plot shows 1024 data points



cut26-30kts-2.5ft: stbd vertical



cut26-30kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.005024 G

Standard deviation = 0.04573 G

The plot shows 1024 data points



cut26-30kts-2.5ft: stbd axial



cut26-30kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004794 G

Standard deviation = 0.07615 G

The plot shows 1024 data points



cut26-30kts-2.5ft: stbd transverse



cut26-30kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.004664 G

Standard deviation = 0.08642 G

The plot shows 1024 data points



cut26-30kts-2.5ft: port vertical



cut26-30kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.005193 G

Standard deviation = 0.09918 G

The plot shows 1024 data points



cut26-30kts-2.5ft: port axial



cut26-30kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.003122 G

Standard deviation = 0.04943 G

The plot shows 1024 data points



cut26-30kts-2.5ft: port transverse



cut27-31kts-2.5ft: stbd vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.01193 G

Standard deviation = 0.1322 G

The plot shows 1024 data points



cut27-31kts-2.5ft: stbd vertical



cut27-31kts-2.5ft: stbd axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.008239 G

Standard deviation = 0.0426 G

The plot shows 1024 data points



cut27-31kts-2.5ft: stbd axial



cut27-31kts-2.5ft: stbd transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003232 G

Standard deviation = 0.07568 G

The plot shows 1024 data points



cut27-31kts-2.5ft: stbd transverse



cut27-31kts-2.5ft: port vertical

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = 0.0001124 G

Standard deviation = 0.07538 G

The plot shows 1024 data points



cut27-31kts-2.5ft: port vertical



cut27-31kts-2.5ft: port axial

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024×10^5

* The time domain


Mean value = -0.003423 G

Standard deviation = 0.0953 G

The plot shows 1024 data points



cut27-31kts-2.5ft: port axial



cut27-31kts-2.5ft: port transverse

Data sampling frequency = 2000 Hz


Total number of sampling data points = 1.024e+005

* The time domain


Mean value = -0.002723 G

Standard deviation = 0.04734 G

The plot shows 1024 data points



cut27-31kts-2.5ft: port transverse



APPENDIX C

SELECTED NARROWBAND TEST DATA
FOR STARBOARD AND PORTSIDE TRIAXIAL TRANSDUCERS

cut2-19kts-1.5ft:stbd vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = 0.01201 G

Standard deviation = 0.152 G

The plot shows 1024 data points



cut2-19kts-1.5ft:stbd vert(narrowband)



cut2-19kts-1.5ft:stbd axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.003854 G

Standard deviation = 0.0374 G

The plot shows 1024 data points



cut2-19kts-1.5ft:stbd axial(narrowband)



cut2-19kts-1.5ft:stbd trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = 0.001539 G

Standard deviation = 0.04871 G

The plot shows 1024 data points



cut2-19kts-1.5ft:stbd trans(narrowband)



cut2-19kts-1.5ft:port vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = 0.005402 G

Standard deviation = 0.08268 G

The plot shows 1024 data points



cut2-19kts-1.5ft:port vert(narrowband)



cut2-19kts-1.5ft:port axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.003198 G

Standard deviation = 0.07836 G

The plot shows 1024 data points



cut2-19kts-1.5ft:port axial(narrowband)



cut2-19kts-1.5ft:port trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.003592 G

Standard deviation = 0.04204 G

The plot shows 1024 data points



cut2-19kts-1.5ft:port trans(narrowband)



cut3-32kts-1.5ft: stbd vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.02035 G

Standard deviation = 0.116 G

The plot shows 1024 data points



cut3-32kts-1.5ft: stbd vert(narrowband)



cut3-32kts-1.5ft: stbd axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.006557 G

Standard deviation = 0.04308 G

The plot shows 1024 data points



cut3-32kts-1.5ft: stbd axial(narrowband)



cut3-32kts-1.5ft: stbd trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.006972 G

Standard deviation = 0.05341 G

The plot shows 1024 data points



cut3-32kts-1.5ft: stbd trans(narrowband)



cut3-32kts-1.5ft: port vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.0121 G

Standard deviation = 0.06898 G

The plot shows 1024 data points



cut3-32kts-1.5ft: port vert(narrowband)



cut3-32kts-1.5ft: port axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.01155 G

Standard deviation = 0.08646 G

The plot shows 1024 data points



cut3-32kts-1.5ft: port axial(narrowband)



cut3-32kts-1.5ft: port trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.005363 G

Standard deviation = 0.0427 G

The plot shows 1024 data points



cut3-32kts-1.5ft: port trans(narrowband)



cut6-36kts-0ft: stbd axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.002894 G

Standard deviation = 0.03688 G

The plot shows 1024 data points



cut6-36kts-0ft: stbd axial(narrowband)



cut6-36kts-0ft: stbd vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.003286 G

Standard deviation = 0.1222 G

The plot shows 1024 data points



cut6-36kts-0ft: stbd vert(narrowband)



cut6-36kts-0ft: stbd trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.003504 G

Standard deviation = 0.04904 G

The plot shows 1024 data points



cut6-36kts-0ft: stbd trans(narrowband)



cut6-36kts-0ft: port axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = 0.0002968 G

Standard deviation = 0.07794 G

The plot shows 1024 data points



cut6-36kts-0ft: port axial(narrowband)



cut6-36kts-0ft: port vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.001617 G

Standard deviation = 0.07307 G

The plot shows 1024 data points



cut6-36kts-0ft: port vert(narrowband)



cut6-36kts-0ft: port trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.0009952 G

Standard deviation = 0.04174 G

The plot shows 1024 data points



cut6-36kts-0ft: port trans(narrowband)



cut12-15kts-0ft: stbd vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = 0.000354 G

Standard deviation = 0.08984 G

The plot shows 1024 data points



cut12-15kts-0ft: stbd vert(narrowband)



cut12-15kts-0ft: stbd axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.0007067 G

Standard deviation = 0.0281 G

The plot shows 1024 data points



cut12-15kts-0ft: stbd axial(narrowband)



cut12-15kts-0ft: stbd trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.006011 G

Standard deviation = 0.0503 G

The plot shows 1024 data points



cut12-15kts-0ft: stbd trans(narrowband)



cut12-15kts-0ft: port vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.0007937 G

Standard deviation = 0.05616 G

The plot shows 1024 data points



cut12-15kts-0ft: port vert(narrowband)



cut12-15kts-0ft: port axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.004243 G

Standard deviation = 0.07873 G

The plot shows 1024 data points



cut12-15kts-0ft: port axial(narrowband)



cut12-15kts-0ft: port trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.001229 G

Standard deviation = 0.03755 G

The plot shows 1024 data points



cut12-15kts-0ft: port trans(narrowband)



cut18-18kts-2.5ft: stbd vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.01738 G

Standard deviation = 0.1067 G

The plot shows 1024 data points



cut18-18kts-2.5ft: stbd vert(narrowband)



cut18-18kts-2.5ft: stbd axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.01694 G

Standard deviation = 0.03401 G

The plot shows 1024 data points



cut18-18kts-2.5ft: stbd axial(narrowband)



cut18-18kts-2.5ft: stbd trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.0171 G

Standard deviation = 0.05827 G

The plot shows 1024 data points



cut18-18kts-2.5ft: stbd trans(narrowband)



cut18-18kts-2.5ft: port vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.007835 G

Standard deviation = 0.07389 G

The plot shows 1024 data points



cut18-18kts-2.5ft: port vert(narrowband)



cut18-18kts-2.5ft: port axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = 0.007301 G

Standard deviation = 0.09301 G

The plot shows 1024 data points



cut18-18kts-2.5ft: port axial(narrowband)



cut18-18kts-2.5ft: port trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.008038 G

Standard deviation = 0.04674 G

The plot shows 1024 data points



cut18-18kts-2.5ft: port trans(narrowband)



cut23-36kts-2.5ft: stbd vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.02906 G

Standard deviation = 0.164 G

The plot shows 1024 data points



cut23-36kts-2.5ft: stbd vert(narrowband)



cut23-36kts-2.5ft: stbd axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.005884 G

Standard deviation = 0.04879 G

The plot shows 1024 data points



cut23-36kts-2.5ft: stbd axial(narrowband)



cut23-36kts-2.5ft: stbd trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.01295 G

Standard deviation = 0.06155 G

The plot shows 1024 data points



cut23-36kts-2.5ft: stbd trans(narrowband)



cut23-36kts-2.5ft: port vert(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.01843 G

Standard deviation = 0.09354 G

The plot shows 1024 data points



cut23-36kts-2.5ft: port vert(narrowband)



cut23-36kts-2.5ft: port axial(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.01183 G

Standard deviation = 0.09632 G

The plot shows 1024 data points



cut23-36kts-2.5ft: port axial(narrowband)



cut23-36kts-2.5ft: port trans(narrowband)

Data sampling frequency = 100 Hz


Total number of sampling data points = 4096

* The time domain


Mean value = -0.005474 G

Standard deviation = 0.04653 G

The plot shows 1024 data points



cut23-36kts-2.5ft: port trans(narrowband)



APPENDIX D

PITCH AND ROLL TEST DATA

cut1-22.5kts-1.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.08096 Degree

Standard deviation = 1.804 Degree

The plot shows 1024 data points



cut1-22.5kts-1.5ft: pitch



cut1-22.5kts-1.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.3369 Degree

Standard deviation = 1.045 Degree

The plot shows 1024 data points



cut1-22.5kts-1.5ft: roll



cut2-19kts-1.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.3519 Degree

Standard deviation = 0.7258 Degree

The plot shows 1024 data points



cut2-19kts-1.5ft: pitch



cut2-19kts-1.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.0378 Degree

Standard deviation = 0.3075 Degree

The plot shows 1024 data points



cut2-19kts-1.5ft: roll



cut3-32kts-1.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.1615 Degree

Standard deviation = 0.4265 Degree

The plot shows 1024 data points



cut3-32kts-1.5ft: pitch



cut3-32kts-1.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.05908 Degree

Standard deviation = 0.4023 Degree

The plot shows 1024 data points



cut3-32kts-1.5ft: roll



cut4-42kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.1776 Degree

Standard deviation = 0.3605 Degree

The plot shows 1024 data points



cut4-42kts-0ft: pitch



cut4-42kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.005444 Degree

Standard deviation = 0.2041 Degree

The plot shows 1024 data points



cut4-42kts-0ft: roll



cut6-36kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.335 Degree

Standard deviation = 0.2035 Degree

The plot shows 1024 data points



cut6-36kts-0ft: pitch



cut6-36kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.002226 Degree

Standard deviation = 0.09836 Degree

The plot shows 1024 data points



cut6-36kts-0ft: roll



cut7-25kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2341 Degree

Standard deviation = 0.174 Degree

The plot shows 1024 data points



cut7-25kts-0ft: pitch



cut7-25kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.007571 Degree

Standard deviation = 0.1286 Degree

The plot shows 1024 data points



cut7-25kts-0ft: roll



cut8-35kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192


* The time domain

Mean value = 0.07238 Degree

Standard deviation = 0.2708 Degree

The plot shows 1024 data points





cut8-35kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.03203 Degree

Standard deviation = 0.1658 Degree

The plot shows 1024 data points



cut8-35kts-0ft: roll



cut9-0kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.02871 Degree

Standard deviation = 0.03487 Degree

The plot shows 1024 data points



cut9-0kts-0ft: pitch



cut9-0kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.04681 Degree

Standard deviation = 0.04323 Degree

The plot shows 1024 data points



cut9-0kts-0ft: roll



cut10-36kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.09969 Degree

Standard deviation = 0.1771 Degree

The plot shows 1024 data points



cut10-36kts-0ft: roll



cut10-36kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2474 Degree

Standard deviation = 0.23 Degree

The plot shows 1024 data points



cut10-36kts-0ft: pitch



cut11-6.2kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192


* The time domain

Mean value = 0.3864 Degree

Standard deviation = 0.1409 Degree

The plot shows 1024 data points





cut11-6.2kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.02842 Degree

Standard deviation = 0.124 Degree

The plot shows 1024 data points



cut11-6.2kts-0ft: roll



cut12-15kts-0ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.5103 Degree

Standard deviation = 0.1173 Degree

The plot shows 1024 data points



cut12-15kts-0ft: pitch



cut13-on land hover: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.1178 Degree

Standard deviation = 0.1045 Degree

The plot shows 1024 data points



cut13-on land hover: pitch



cut12-15kts-0ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.1103 Degree

Standard deviation = 0.144 Degree

The plot shows 1024 data points



cut12-15kts-0ft: roll



cut13-on land hover: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.08604 Degree

Standard deviation = 0.07024 Degree

The plot shows 1024 data points



cut13-on land hover: roll



cut14-on land hover: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.1865 Degree

Standard deviation = 0.1153 Degree

The plot shows 1024 data points



cut14-on land hover: pitch



cut15-30.8kts-1ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2476 Degree

Standard deviation = 0.4579 Degree

The plot shows 1024 data points



cut15-30.8kts-1ft: pitch



cut14-on land hover: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.0202 Degree

Standard deviation = 0.04972 Degree

The plot shows 1024 data points



cut14-on land hover: roll



cut15-30.8kts-1ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.07879 Degree

Standard deviation = 0.232 Degree

The plot shows 1024 data points



cut15-30.8kts-1ft: roll



cut16-27kts-2ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2249 Degree

Standard deviation = 0.4391 Degree

The plot shows 1024 data points



cut16-27kts-2ft: pitch



cut16-27kts-2ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.1441 Degree

Standard deviation = 0.657 Degree

The plot shows 1024 data points



cut16-27kts-2ft: roll



cut17-35kts-2ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2322 Degree

Standard deviation = 0.5317 Degree

The plot shows 1024 data points



cut17-35kts-2ft: pitch



cut17-35kts-2ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.05963 Degree

Standard deviation = 0.3872 Degree

The plot shows 1024 data points



cut17-35kts-2ft: roll



cut18-18kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.4381 Degree

Standard deviation = 0.5344 Degree

The plot shows 1024 data points



cut18-18kts-2.5ft: pitch



cut18-18kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.08459 Degree

Standard deviation = 0.5632 Degree

The plot shows 1024 data points



cut18-18kts-2.5ft: roll



cut19-8kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.3557 Degree

Standard deviation = 0.4101 Degree

The plot shows 1024 data points



cut19-8kts-2.5ft: pitch



cut19-8kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.09997 Degree

Standard deviation = 0.4634 Degree

The plot shows 1024 data points



cut19-8kts-2.5ft: roll



cut20-16kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.4596 Degree

Standard deviation = 0.4844 Degree

The plot shows 1024 data points



cut20-16kts-2.5ft: pitch



cut20-16kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.06888 Degree

Standard deviation = 0.3014 Degree

The plot shows 1024 data points



cut20-16kts-2.5ft: roll



cut21-25kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.4181 Degree

Standard deviation = 0.4755 Degree

The plot shows 1024 data points



cut21-25kts-2.5ft: pitch



cut21-25kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.1043 Degree

Standard deviation = 0.4681 Degree

The plot shows 1024 data points



cut21-25kts-2.5ft: roll



cut22-10kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192


* The time domain

Mean value = 0.4982 Degree

Standard deviation = 0.2393 Degree

The plot shows 1024 data points





cut22-10kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

• The time domain


Mean value = -0.0431 Degree

Standard deviation = 0.4245 Degree

The plot shows 1024 data points



cut22-10kts-2.5ft: roll



cut23-36kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.1134 Degree

Standard deviation = 0.9591 Degree

The plot shows 1024 data points



cut23-36kts-2.5ft: pitch



cut23-36kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.1349 Degree

Standard deviation = 0.6546 Degree

The plot shows 1024 data points



cut23-36kts-2.5ft: roll



cut24-22kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2186 Degree

Standard deviation = 0.9433 Degree

The plot shows 1024 data points



cut24-22kts-2.5ft: pitch



cut24-22kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.04645 Degree

Standard deviation = 0.6464 Degree

The plot shows 1024 data points



cut24-22kts-2.5ft: roll



cut25-25kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2431 Degree

Standard deviation = 0.671 Degree

The plot shows 1024 data points



cut25-25kts-2.5ft: pitch



cut25-25kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.01234 Degree

Standard deviation = 0.835 Degree

The plot shows 1024 data points



cut25-25kts-2.5ft: roll



cut26-30kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.2005 Degree

Standard deviation = 0.6042 Degree

The plot shows 1024 data points



cut26-30kts-2.5ft: pitch



cut26-30kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.02648 Degree

Standard deviation = 0.5728 Degree

The plot shows 1024 data points



cut26-30kts-2.5ft: roll



cut27-31kts-2.5ft: pitch

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = 0.232 Degree

Standard deviation = 0.5933 Degree

The plot shows 1024 data points



cut27-31kts-2.5ft: pitch



cut27-31kts-2.5ft: roll

Data sampling frequency = 100 Hz


Total number of sampling data points = 8192

* The time domain


Mean value = -0.03554 Degree

Standard deviation = 0.3809 Degree

The plot shows 1024 data points



cut27-31kts-2.5ft: roll



INITIAL DISTRIBUTION LIST

		No. of Copies
1.	Defense Technical Information Center Cameron Station Alexandria, Virginia 22304-6145	2
2.	Library, Code 52 Naval Postgraduate School Monterey, California 93943-5002	2
3.	Naval Engineering Curricular Office, Code 34 Naval Postgraduate School Monterey, California 93943-5000	1
4.	Professor Y. S. Shin, Code ME/Sg Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93943	2
5.	Dr. E. Michael Golda Carderock Division, Naval Surface Warfare Center Annapolis Detachment Code 812 Annapolis, MD 21042-5067	3
6.	Mr. Thomas Fikse Carderock Division, Naval Surface Warfare Center Annapolis Detachment Code 812 Annapolis, MD 21042-5067	1
7.	Mr. Edward Thomas Carderock Division, Naval Surface Warfare Center Annapolis Detachment Code 812 Annapolis, MD 21042-5067	1
8.	Eric Hoy, LT USN Naval Engineering Curricular Office, Code 34 Naval Postgraduate School Monterey, California 93943-5000	1

DUDLEY KNOX LIBRARY



3 2768 00331626 6